

RediFrame

RediFrame Fixed Frame

RediFrame is a prefinished fixed throat steel door frame designed for interior and exterior applications.

Features

- 1-3/4" thick doors
- 18 or 20 gauge steel (depending on wall size), casing is 22 gauge
- 5/8" stop height
- Demountable without damage to the finished wall, door or frame
- Frame is cold-rolled steel per ASTM A366
- 2-3/4" T strike prep
- Embossed 90 minute neutral and positive pressure fire label wood or steel stud

Code Compliance/Certification

- ANSI 250.5-1994 Certification to Level A1,000,000 cycles
- ULIOB and ULIOC

Options

- ASA 4-7/8" adjustable strike prep (handed)
- No casing option for wood application, no lances
- "J" frame option, 80-3/4" height (Ivory and Brown 4-7/8" wall only)



Stocked Product

Heads - Brown/Ivory

- Wall Sizes: 4-7/8", 5-3/8"
- Lengths: 2'0", 2'4", 2'6", 2'8", 2'10", 3'0"
- Wall Sizes: 6-3/4", 7-1/4"
- Lengths: 3'0", 6'0"

Heads - Alusteel/Black

- Wall Sizes: 4-7/8", 5-3/8"
- Lengths: 3'0"

Jambs - Brown/Ivory

- Wall Sizes: 4-7/8", 5-3/8", 6-3/4", 7-1/4"
- Lengths: 6'8", 7'0"

Jambs - Alusteel

- Wall Sizes: 4-7/8", 5-3/8"
- Lengths: 6'8", 7'0"

Jambs - Black

- Wall Sizes: 4-7/8", 5-3/8"
- Lengths: 6'8"
- Wall Sizes: 4-7/8", 5-3/8", 6-3/4", 7-1/4"
- Lengths: 7'0"

RediFrame

Kerf RediFrame Fixed Frame for Weatherstripping

Kerf profile option for RediFrame is a fixed steel door frame designed for interior and exterior applications.

Features

- 1-3/4" thick doors
- 18 or 20 gauge steel (depending on wall size), casing is 22 gauge
- 5/8" stop height
- Demountable without damage to the finished wall, door or frame
- Frame is cold-rolled steel per ASTM A366
- 2-3/4" T strike prep
- Embossed 90 minute neutral and positive pressure fire label wood or steel stud

Code Compliance/Certification

- ANSI 250.5-1994 Certification to Level A1,000,000 cycles
- ULIOB and ULIOC

Options

- ASA 4-7/8" adjustable strike prep (handed)
- No casing option for wood application, no lances



Stocked Product

Finishes	4-7/8"	5-3/8"
Brown	X	X
Ivory	X	X

- Wall Size: 4-7/8" and 5-3/8"
- Hinge prep: 4" and 4-1/2"
- Header width: 3'0" only
- Pair Doors width: 6'0"
- Height: 6'8" and 7'0"

RediFrame

RediFlex Adjustable Frame

RediFlex is an adjustable throat steel door frame designed for interior and exterior applications where varying wall sizes must be accommodated and for pre hanging.

Features

- 1-3/4" thick door only
- 18 or 20 gauge steel (depending on wall size), casing is 22 gauge
- 5/8" stop height
- Demountable without damage to the finished wall, door or frame
- Frame is cold-rolled steel per ASTM A366
- 2-3/4" T strike prep
- Embossed 90 minute neutral and positive pressure fire label wood or steel stud

Code Compliance/Certification

- ANSI 250.5-1994 Certification to Level A1,000,000 cycles
- ULIOB and ULIOC

Options

- ASA 4-7/8" adjustable strike prep (handed)
- No casing option for wood application, no lances



Stocked Product

Finishes/ Wall Size	4 - 5-1/4"	5 - 6-1/4"	6 - 7-1/4"	7 - 8-1/4"	8 - 9-1/4"	9 - 10-1/4"
Brown	X	X	X	X	X	X
Ivory	X	X	X	X	X	X

- Hinge prep: 4" and 4-1/2"
- Height: 6'8", 7'0" Brown, Ivory
7'0" Brown only
- Header width: 3'0" only
- Pair Doors width: 6'0"